

TECHNICAL SPECIFICATIONS

PARAMETERS	IDU MODEL NUMBER	ASGG12CGWA-B (R32)
Bee Star Rating		4
Tonnage	TR	1.00(0.50-1.090)
Power Supply	PH-HZ-V	1P-50-230
Running Current	A	3.9
Standard Cooling At 100% Capacity	W	3500(1750-3850)
Standard Cooling At 50% Capacity	W	1,750
Power Consumption At 100% Capacity	W	850(320-952)
Power Consumption At 50% Capacity	W	320
Eer At 100% Capacity	WW	4.12
Err At 50% Capacity	W/W	5.47
Rated Iseer	KWh/kWh	5.15
Electricity Consumption At Annum	KWh	526.59
Mooisture Removal	l/h	0.7
Indoor Fan Speed Control Level		6
Indoor Airflow Volume Powerful	m3/h	780
Indoor Airflow Distance	M	10
Indoor Unit Dimensions H*W*D	mm	295*804*288
Indoor Unit Net Weight	kg	9.5
Outdoor Unit Dimensions H*W*D	mm	594*810*301
Outdoor Unit Net Weight	kg	33.00
Indoor Noise Level	db(A)	36
Connection Pipe(Gas /Liquid)	mm	12.70/6.35
Operating Voltage Range	v	195V-265V
Refrigerant Type	non-CFC	R32
Compressor Type		TROPICAL ROTARY
Evaporator & Condenser Coilmaterial		COPPER