

TECHNICAL SPECIFICATIONS

PARAMETERS	IDU MODEL NUMBER	ASGG18CKAA-B
Bee Star Rating		3
Tonnage	TR	1.51(0.75-1.55)
Power Supply	PH-HZ-V	1p-50-230
Running Current	A	6.8
Standard Cooling At 100% Capacity	W	5300(2650-5450)
Standard Cooling At 50% Capacity	W	2,650
Power Consumption At 100% Capacity	W	1,480(552-1550)
Power Consumption At 50% Capacity	W	552
Eer At 100% Capacity	WW	3.58
Err At 50% Capacity	W/W	4.80
Rated Iseer	KWh/kWh	4.50
Electricity Consumption At Annum	KWh	912.24
Mooisture Removal	l/h	1.4
Indoor Fan Speed Control Level		6
Indoor Airflow Volume Powerful	m3/h	1050
Indoor Airflow Distance	M	15
Indoor Unit Dimensions H*W*D	mm	295*1000*230
Indoor Unit Net Weight	kg	11
Outdoor Unit Dimensions H*W*D	mm	555*780*281
Outdoor Unit Net Weight	kg	26.5
Indoor Noise Level	db(A)	39
Connection Pipe(Gas /Liquid)	mm	12.70/6.35
Operating Voltage Range	v	145v-285v
Refrigerant Type	non-CFC	R32
Compressor Type		TROPICAL ROTARY
Evaporator & Condenser Coilmaterial		COPPER