

TECHNICAL SPECIFICATIONS

PARAMETERS	IDU MODEL NUMBER	ASGG24CKWA-B
Bee Star Rating		3
Tonnage	TR	2.00(1.00-2.06)
Power Supply	PH-HZ-V	1P-50-230
Running Current	A	9.6
Standard Cooling At 100% Capacity	W	7050(3525-7260)
Standard Cooling At 50% Capacity	W	3,525
Power Consumption At 100% Capacity	W	2100(695-2205)
Power Consumption At 50% Capacity	W	695
Eer At 100% Capacity	WW	3.35
Err At 50% Capacity	W/W	5.07
Rated Iseer	KWh/kWh	4.50
Electricity Consumption At Annum	KWh	1213.80
Mooisture Removal	l/h	2.4
Indoor Fan Speed Control Level		6
Indoor Airflow Volume Powerful	m3/h	1300
Indoor Airflow Distance	M	15
Indoor Unit Dimensions H*W*D	mm	330*1100*250
Indoor Unit Net Weight	kg	14
Outdoor Unit Dimensions H*W*D	mm	645*810*301
Outdoor Unit Net Weight	kg	37.5
Indoor Noise Level	db(A)	41
Connection Pipe(Gas /Liquid)	mm	12.70/6.35
Operating Voltage Range	v	145V-285V
Refrigerant Type	non-CFC	R32
Compressor Type		TROPICAL TWIN ROTARY
Evaporator & Condenser Coilmaterial		COPPER