

TECHNICAL SPECIFICATIONS

PARAMETERS	IDU MODEL NUMBER	ASGG24CGWA-B (R32)
Bee Star Rating		4
Tonnage	TR	2.00(1.00-2.10)
Power Supply	PH-HZ-V	1p-50-230
Running Current	A	7.8
Standard Cooling At 100% Capacity	W	7050(3525-7385)
Standard Cooling At 50% Capacity	W	3,525
Power Consumption At 100% Capacity	W	1745(635-1880)
Power Consumption At 50% Capacity	W	645
Eer At 100% Capacity	WW	4.04
Err At 50% Capacity	W/W	5.46
Rated Iseer	KWh/kWh	5.10
Electricity Consumption At Annum	KWh	1070.32
Mooisture Removal	l/h	1.8
Indoor Fan Speed Control Level		6
Indoor Airflow Volume Powerful	m3/h	1450
Indoor Airflow Distance	M	15
Indoor Unit Dimensions H*W*D	mm	330*1100*250
Indoor Unit Net Weight	kg	14.00
Outdoor Unit Dimensions H*W*D	mm	752*910*330
Outdoor Unit Net Weight	kg	49.50
Indoor Noise Level	db(A)	44
Connection Pipe(Gas /Liquid)	mm	15.88/6.35
Operating Voltage Range	v	195v-265v
Refrigerant Type	non-CFC	R32
Compressor Type		TROPICAL TWIN ROTARY
Evaporator & Condenser Coilmaterial		COPPER