

TECHNICAL SPECIFICATIONS

PARAMETERS	IDU MODEL NUMBER	ASGG12CKAA-B
Bee Star Rating		3
Tonnage	TR	1.0(0.50-1.04)
Power Supply	PH-HZ-V	1P-50-230
Running Current	A	4.5
Standard Cooling At 100% Capacity	W	3,550(1775-3650)
Standard Cooling At 50% Capacity	W	1,775
Power Consumption At 100% Capacity	W	980(373-1030)
Power Consumption At 50% Capacity	W	373
Eer At 100% Capacity	WW	3.62
Err At 50% Capacity	W/W	4.76
Rated Iseer	KWh/kWh	4.5
Electricity Consumption At Annum	KWh	610.76
Mooisture Removal	l/h	1.00
Indoor Fan Speed Control Level		6
Indoor Airflow Volume Powerful	m3/h	700
Indoor Airflow Distance	M	10
Indoor Unit Dimensions H*W*D	mm	295*800*230
Indoor Unit Net Weight	kg	9.5
Outdoor Unit Dimensions H*W*D	mm	557*780*241
Outdoor Unit Net Weight	kg	24
Indoor Noise Level	db(A)	34
Connection Pipe(Gas /Liquid)	mm	9.52/6.35
Operating Voltage Range	v	145v-258v
Refrigerant Type	non-CFC	R32
Compressor Type		tropical rotary
Evaporator & Condenser Coilmaterial		Copper